



CANT.	SIMBOLO	DESCRIPCION
128 UD.	D	OPPLE PANEL 595 UGR 19 30W DALI. / PHILIPS RC132V PSD W60L60 1 xLED36S/840 OC
0 UD.		OPPLE PANEL 595 UGR 19 30W .
17 UD.		OPPLE PANEL 595 UGR 22 34W / PHILIPS RC132V W60L60 1 xLED36S/840 NOC
0 UD.		OPPLE MW R200 15W
20 UD.	O	OPPLE ECOMAX R200 24W (SI HAY FALSO TECHO) / PHILIPS DN 135 LED 20S/840 28W(DE SUPERFICIE - ASEOS)
13 UD.	O	OPPLE ECOMAX R150 12W (SI HAY FALSO TECHO) / PHILIPS DN 135 LED 10S/830 13W(DE SUPERFICIE-ASEOS)
1 UD.		LED WATERPROOF-F 1550 57 W 4000 FR 2X58 W/

CANT.	SIMBOLO	DESCRIPCION
10	D	CONTROLADOR PHILIPS OCCUSWITCH DALI AVANZADO LRM 2090
08		DETECTOR DE MOVIMIENTO INDEPENDIENTE PHILIPS OCCUSWITCH MOD. LRM1070/00 SI NO EXISTE FALSO TECHO ES NECESARIO EL ACCESORIO LRH 2070 PARA SUSPENDER O ADOSAR A UNA ALTURA APROX. DE 2,8M
12		DETECTOR DE MOVIMIENTO PHILIPS MOD. LRM1011