



LEYENDA DE LUMINARIAS		
CANT.	SÍMBOLO	DESCRIPCIÓN
47 UD.		OPPLE PANEL 595 UGR 19 30W EMPOTRADA LEDPanelRc-S4-Sq595-30W-DALJ4000-WH-U19
81 UD.		OPPLE PANEL 595 UGR 22 34W EMPOTRADA LEDPanelRc-S4-Sq595-34W-4000-WH-U22
317 UD.		OPPLE PANEL 595 UGR 19 30W SUPERFICIE LEDPanelRc-S4-Sq595-30W-DALJ4000-WH-U19
93 UD.		OPPLE PANEL 595 UGR 22 34W SUPERFICIE LEDPanelRc-S4-Sq595-34W-4000-WH-U22
25 UD.		OPPLE ESTANCA LED ECOMAX 57W LEDWaterproof-Ec-1150-57W-4000-FR
30 UD.		OPPLE ESTANCA LED ECOMAX 43W LEDWaterproof-Ec-1150-43W-4000-FR
1 UD.		OPPLE ESTANCA LED ECOMAX 23W LEDWaterproof-Ec-650-23W-4000-FR
4 UD.		OPPLE Downlight LEDDownlightRc-SHE-Rd200-24W-3000-WH

LEYENDA DEL SISTEMA DE CONTROL		
CANT.	SÍMBOLO	DESCRIPCIÓN
34		CONTROLADOR PHILIPS OCCUSWITCH DALI8SM LRM 2090
16		DETECTOR DE MOVIMIENTO INDEPENDIENTE PHILIPS OCCUSWITCH MOD. LRM1070.00 3 INDICADORES ALISO TILCHO ES NEESSARD EL ACCESORIO LRM 2010 PARA SUPLENIR O ADOSSAR A UNA ALTURA MÍNIMA DE 2M
		PANELES FONDOABSORBENTES